

PS	VALUE GUIDE	BILGE PUMPS, 1600 GPH and up						
MAKER	RULE		SHURFLO	ATTWOOD		JOHNSON		
MODEL	10 (2,000)	Rule-Mate 2000	358-010-00 (2000) ★	4030 \$ (HD 1700)	4060 (HD 2000)	1600	2200	4000
PRICE	\$93	\$173	\$90	\$84	\$93	\$54	\$63	\$124
OUTLET PIPE SIZE	1 1/8 in.	1 1/8 in.	1 1/8 in.	1 1/8 in.	1 1/8 in.	1 1/8 in.	1 1/8 in.	1 1/2 in.
WEIGHT	2 lbs., 14.9 oz.	3 lbs., 13 oz.	4 lbs., 13.8 oz.	3 lbs., 4.1 oz.	3 lbs., 11 oz.	2 lbs., 15.7 oz.	5 lbs., 1 oz.	5 lbs., 7.9 oz.
FUSE SIZE	15 amps	15 amps	15 amps	10 amps	12 amps	10 amps	15 amps	20 amps
WIRE SIZE AWG	16	16	16	16	16	16	16	14
LEAD LENGTH	29 in.	46 in.	60 in.	32 in.	32 in.	68 in.	68 in.	68 in.
WARRANTY	3 yr. limited	3 yr. limited	3 yr. limited	3 yr. (rec.); 1 yr. (comm.)	3 yr. (rec.); 1 yr. (comm.)	18 mos. limited	18 mos. limited	18 mos. limited
OUTLET OPTIONS	2 positions	2 positions	360 degrees	4 positions	4 positions	2 positions	2 positions	2 positions
DRY RUN MAX TEMP	177 degrees	153 degrees	115 degrees	115 degrees	149 degrees	103 degrees	101 degrees	103 degrees
CLAIMED GPH 3.35 (1 M.) @ 13.6 v / 12v	1620 / 1450	1620 / 1450	2000 / NA	1,300 / NA	1,500 / NA	1550 / 1400	1900 / 1750	3100 / 2600
TESTED GPH @ 13.6v / 12.2v	1,334 / 1,200	1,242 / 1,059	1,800 / 1,637	1,242 / 1029	1,385 / 1200	766 / 642	1,125 / 1,027	1,637 / 1,566
AMP DRAW @ 13.6 v / 12.2v	7 amps / 6.8 amps	7.3 amps / 6.3 amps	8.8 amps / 7.2 amps	5.6 amps / 4.7 amps	7.4 amps / 5.5 amps	5 amps / 3.9 amps	7.5 amps / 6.4 amps	9.8 amps / 8.2 amps
PUMPING TIME (10 GALLONS) @ 13.6 v / 12.2v	27 seconds / 30 seconds	29 seconds / 34 seconds	20 seconds / 22 seconds	29 seconds / 35 seconds	26 seconds / 30 seconds	47 seconds / 56 seconds	32 seconds / 35 seconds	22 seconds / 23 seconds
COMMENTS	Hottest pump during break-in; couldn't keep hand on case.	Automatic with built in float.	Noticeably heavier than others; labeled as a 2000, but claims 2200 at open flow; unique 360 mount.	Has twist-and-lock style mounting base.	Has twist-and-lock style mounting base.		Also provides fitting for 1 1/2-inch discharge hose; tested with 1 1/8 in. hose.	Also provides fitting for 2-inch discharge hose; tested with 1 1/2 in. hose.

★ Best Choice    \$ Budget Buy